



**AMCOL Corporation**

Proven technology, refined over decades.

# 918 1KO CANT RUST

Water Displacing Corrosion Preventative

## PRODUCT DESCRIPTION

**918 1KO CANT RUST** is a solvent carried liquid corrosion inhibitor designed to protect fabricated steel profiles during indoor storage and transit.

This product provides uniform coverage across the entire surface of the part, effectively preventing rust, staining, and corrosion. **918 1KO CANT RUST** is also suitable for protecting galvanized and aluminized surfaces.

## ADVANTAGES:

- **Excellent Corrosion Prevention**
- **Easily Removed for Painting and Plating**
- **Light Residual Near Dry Film**
- **May Be Spray Applied**

## COMMON APPLICATIONS:

- **Welded Tubes**
- **Cold-rolled Steel Profiles**
- **Metal Stampings**
- **Fabricated Steel Parts**



**AMCOL Corporation**

Proven technology, refined over decades.

# 918 1KO CANT RUST

Water Displacing Corrosion Preventative



## METHOD OF APPLICATION AND CLEANING

The **918 1KO CANT RUST** storage coatings are most often spray applied to steel profiles using automated spray equipment. AMCOL's Model 3200S In-line Spray Applicator is designed for use on tube mills to ensure a consistent coating of tubes coming off the machine. Coatings can also be applied by manual spray wand or immersion methods.

One gallon of **918 1KO CANT RUST** provides light coverage for up to 10,000 ft<sup>2</sup> of steel. For long-term storage protection, a heavier application is recommended — covering approximately 3,000 ft<sup>2</sup> per gallon.

### Cleaning:

**918 1KO CANT RUST** is easily removed using acid or alkaline detergent cleaners, mineral spirits, or vapor degrease.

## TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid at 25 deg C

Odor and Appearance: Brown liquid with a petroleum odor

Solubility (in water): Insoluble

Specific Gravity: 0.80-0.90

pH: n/a

Viscosity: 1-50 centipoise at 25 deg C

Special Precautions: None



**AMCOL Corporation**  
21435 Dequindre  
Hazel Park, MI 48030  
248-414-5700  
fx. 248-414-7489  
[www.amcolcorp.com](http://www.amcolcorp.com)

PS02.918.PB  
Approved for Use  
LSB: AA0014  
LSD: 07/17/2025